



CIRCUIT SIZE LAYOUT

Poles	Dimensions (mm)		
	A	B	C
2x01	--	6.65	4.30
2x02	3.00	9.65	7.30
2x03	6.00	12.65	10.30
2x04	9.00	15.65	13.30
2x05	12.00	18.65	16.30
2x06	15.00	21.65	19.30
2x07	18.00	24.65	22.30
2x08	21.00	27.65	25.30
2x09	24.00	30.65	28.30
2x10	27.00	33.65	31.30
2x11	30.00	36.65	34.30
2x12	33.00	39.65	37.30

P.C.B Layout: TOP VIEW
Tolerance: ±0.05mm

- SPECIFICATIONS**
- Voltage rating: 250V AC, DC
 - Current rating: 5A, AC, DC
 - Withstanding Voltage: 1000V AC/minute
 - Insulation resistance: 1000MΩ min
 - Temperature range: -40° C~+105° C
 - Contact resistance: 20mΩ max
- WAFER**
- Part No. : 3045WRS-2xNP-L
 - Poles : 02-24P
 - Housing Material: LCP UL94V-0 Black
 - Ter Material: Brass
 - Solder Tabs Material: Brass
 - Contact Area Plating: Matte Tin-Plated
 - The Dimension Marked “▼” Must Be Recorded

APPROVALS		DATE	TITLE:	
DRAWN	ZHIWEI.CHEN	2015.07.07	3.0mm SMT 90° 鱼叉式	
CHECKED			PART NO. GP01-3045WRS-2xNP-L	
APPROVALS			SCALE: 1:1	
TOLERANCES ARE		ANGLE	UNIT: mm	PROJ:
30~以上	±0.30	±2°		
10~30	±0.20		DRAWING NO.	
5~10	±0.15			
~5	±0.10			
ECN NO.	REV.	DATE.	DESCRIPTION.	SHEET
	A		NEW	1 OF 1



深圳市联盈电子有限公司
SHENZHEN LIANYING ELECTRONIC CO.,LTD