



P.C.B LAYOUT

Technical Data
 Material: Brass,machined CuZn38Pb2
 Pin(outer sleeve):Brass,machined CuZn38Pb2
 Plating(outer sleeve):
 Tin Plated:2 μ m/80 μ m "Ni,5 μ m/200 μ "Sn
 Gold Plated:2 μ m"/80 μ m "Ni,0.8 μ " gold
 Insulator: PPS UL94V-0

Electrical:
 Current rating: 3Amps/contact max.
 Contact resistance: $\leq 4m\Omega$ /contact
 Insulation resistance: $\geq 1000M\Omega$ at V=100V
 Operating voltage: 60VAC/DC

Mechanical:
 Operating temperature: -40°C to+105°C
 Soldering temperature: +255°C

ECN NO.	REV.	DATE.	DESCRIPTION.	CHANGE.	CHECK.	APPRO.
	A		NEW			

APPROVALS		DATE	深圳市联丰电子有限公司 SHENZHEN LIANFENG ELECTRONIC CO.,LTD			
DRAWN	ZHIWEI.CHEN	2015.07.07	TITLE:	2.54MM IC 圆孔插针	PART NO.	GP28-0762-2XNP-1196A
CHECKED			PART NO.		SCALE:	1:1
APPROVALS			UNIT:	mm	PROJ:	
TOLERANCES ARE			ANGLE	±2°	DRAWING NO.	
30~以上	±0.30					
10~30	±0.20					
5~10	±0.15					
~5	±0.10					
SHEET			1	OF	1	