



备注(Remark)

1.材料(MATERIAL)

胶芯:PA6T/PBT+30%G.F UL94V-0,颜色:黑色.

Housing: PA6T+30%G.F UL94V-0,Color: Black 黄铜,

端子:镍底30u"MIN,表面镀金1u"MIN

Contact: Brass,0.8u"MIN GOLD PLATING OVERALL

30u" MIN NICKEL UNDERPLATING OVER ALL

2.特性(characteristics):

额定电流: 2AMP

Raring Current: 2AMP.

接触阻抗: 20 MΩ MAX.

Contact Resistance: 20 MΩ MAX.

绝缘阻抗: 1000 MΩ MIN.

Insulating Resistance: 1000 MΩ MIN.

耐电压: AC 500V.

Withstanding Voltage:AC 500V.

温度范围:-40°C to+105°C

Temperature Range:-40°C to+105°C

Plastic Base

Type	
H	4.0
PA	2.8
PB	0
PC	2.8

PCB LAYOUT

ECN NO.	REV.	DATE.	DESCRIPTION.	CHANGE	CHECK.	APPRO.
	A		NEW			

APPROVALS		DATE	<p>深圳市联丰电子有限公司 SHENZHEN LINFENYING ELECTRONIC CO.,LTD</p>			
DRAWN	ZHIWEI.CHEN	2015.07.07	TITLE:	2.0mm 成型弯针	PART NO.	GP26-2020WR-CS-2xNP
CHECKED			UNIT:	mm	SCALE:	1:1
APPROVALS			DRAWING NO.		PROJ:	
TOLERANCES ARE			30 <sup>以上</sup>	±0.30	ANGLE	±2°
			10~30	±0.20		
			5~10	±0.15		
			~ 5	±0.10		
SHEET 1 OF 1						