



SPECIFICATIONS
 Current Rating: 3A AC,DC
 Voltage Rating: 250V AC,DC
 Temperature Range: -25°C ~ +85°C
 Contact Resistance: 20mΩ Max
 Insulation Resistance: 1000MΩ Min
 Withstanding Voltage: 1500V AC/minute
 Pin Material: Brass/Gold-flash
 Material: PBT15%GF,UL94V-0
 Color: Natural(Black)

Ordering Information & Dimensions

PART NO.	Dimensions	
	A	B
2X03P	5.08	15.24
2X04P	7.62	17.78
2X05P	10.16	20.32
2X06P	12.70	22.86
2X07P	15.24	25.40
2X08P	17.78	27.94
2X10P	22.86	33.02
2X12P	27.94	38.10
2X13P	30.48	40.64
2X15P	35.56	45.72
2X17P	40.64	50.80
2X20P	48.26	58.42
2X22P	53.34	63.50
2X24P	58.42	68.58
2X25P	60.96	71.12
2X30P	73.66	83.82
2X32P	78.74	88.90

ECN NO.	REV.	DATE.	DESCRIPTION.	CHANGE.	CHECK.	APPRO.
	A		NEW			

APPROVALS		DATE	TITLE:	
DRAWN	ZHIWEI.CHEN	2015.07.07	2.54mm Crimp Style Connector	
CHECKED			PART NO.	GP23-2523WR-2XNP
APPROVALS			SCALE:	1:1
TOLERANCES ARE		ANGLE	UNIT:	mm
30~以上	±0.30	±2°	DRAWING NO.	
10~30	±0.20			
5~10	±0.15			
~ 5	±0.10			



深圳市联丰电子有限公司
 SHENZHEN LIANFENG ELECTRONIC CO.,LTD