



PCB Layout Diagram
Top View

NOTE:

1. MATERIAL:

- a. HOUSING: THERMOPLASTIC GLASS FIBRE UL94V-0
- b. CONTACT: PHOSPHOR BRONZE
(SURFACE PLATING: Sn100U")

SEE ORDERING INFORMATION

2. ELECTRIC:

- a. CONTACT RESISTANCE: 30 MILLIOHMS MAX
- b. INSULATION RESISTANCE: 1000 MEGA OHMS MIN
- c. DIELECTRIC VOLTAGE: 500V AC ONE SEC LEVEL
- d. OPERATING TEMPERATURE: -25 ° C ~ +85 ° C

3	TERMINAL (-)	1	PHOSPHOR BRONZE, T=0.15MM	Sn-Plating
2	TERMINAL (+)	1	PHOSPHOR BRONZE, T=0.15MM	Sn-Plating
1	HOUSING	1	LCP	WHITE
NO.	PART NAME	Q'TY	MATERIAL	PLATING & COLOR
ECN NO.	REV.	DATE.		

APPROVALS		DATE	TITLE:	
DRAWN	ZHIWEI.CHEN	2015.07.07	电池座 SN SMT	
CHECKED			PART NO. GP07-CR2032-12	
APPROVALS			SCALE: 1:1	
TOLERANCES ARE		30~以上 ±0.30	ANGLE	±2°
		10~30 ±0.20	UNIT: mm	
		5~10 ±0.15	SCALE: 1:1	PROJ.
		~ 5 ±0.10	DRAWING NO.	
CHANGE.	CHECK.	APPRO.		SHEET 1 OF 1



深圳市联盈电子有限公司
SHENZHEN LIANYING ELECTRONIC CO.,LTD