



PCB Layout Diagram
Top View

NOTE:

1. MATERIAL:

- a. HOUSING: THERMOPLASTIC GLASS FIBRE UL94V-0
- b. CONTACT: PHOSPHOR BRONZE
(SURFACE PLATING: Ni100u")

SEE ORDERING INFORMATION

2. ELECTRIC:

- a. CONTACT RESISTANCE: 30 MILLIOHMS MAX
- b. INSULATION RESISTANCE: 1000 MEGA OHMS MIN
- c. DIELECTRIC VOLTAGE: 500V AC ONE SEC LEVEL
- d. OPERATING TEMPERATURE: -25° C ~ +85° C

ORDERING INFORMATION

3	TERMINAL (-)	1	PHOSPHOR BRONZE, T=0.20MM	Ni-Plating
2	TERMINAL (+)	1	PHOSPHOR BRONZE, T=0.40MM	Ni-Plating
1	HOUSING	1	PBT	BLACK
NO.	PART NAME	Q'TY	MATERIAL	PLATING & COLOR

ECN NO.	REV.	DATE.	DESCRIPTION.	CHANGE.	CHECK.	APPRO.
	A		NEW			

APPROVALS		DATE	TITLE:			
DRAWN	ZHIWEI.CHEN	2015.07.07	PART NO.	GP07-CR2477-01	SCALE:	1:1
CHECKED			UNIT:	mm	PROJ:	
APPROVALS			DRAWING NO.		SHEET	1 OF 1
TOLERANCES ARE						
30~以上	±0.30	ANGLE				
10~30	±0.20					
5~10	±0.15	±2°				
~ 5	±0.10					



深圳市联丰电子有限公司
SHENZHEN LINFENG ELECTRONIC CO.,LTD

电池座