

PC Board Layout
Component Side Shown

NOTES:

MATERIAL:

- 1.HOUSING MATERIAL :GLASS FILLED POLYESTER UL94V-0.
- 2.CONTACT MATERIAL :PHOSPHOR BRONZE φ0.45mm.
- 3.PLATING :GOLD PLATING F_U 50"OVER NICKEL.

ELECTRICAL:


- 1.VOLTAGE RATING :125 VAC RMS.
- 2.CURRENT RATING :15 AMP.
- 3.CONTACT RESISTANCE :30 MILLIOHMS MAX.
- 4.INSULATION RESISTANCE :500 MEGOHMS MIN @ 500V DC .
- 5.DIELECTRIC WITHSTANDING RESISTANCE :1000V AC RMS 50HZ. 1MIN.


MECHANICAL:

- 1.DURRABILITY :750 CYCLES MIN.
- 2.PCB RETENTION PRE-SOLDER :1 LB MIN.

ENVIRONMENTAL:

- 1. STORAGE : -40℃~+85℃
- 2. OPERATION : 0℃ TO 70℃

APPROVALS		DATE	 深圳市联丰电子有限公司 SHENZHEN LINFENGYING ELECTRONIC CO.,LTD	
DRAWN	ZHIWEI CHEN	2015.07.07		
CHECKED				
APPROVALS				

ECN NO.	REV.	DATE.	DESCRIPTION.	CHANGE.	CHECK.	APPRO.																				
	A		NEW																							
TOLERANCES ARE <table border="1"> <tr> <td>30°</td> <td>ØL</td> <td>±0.30</td> <td>ANGLE</td> <td>±2°</td> </tr> <tr> <td>10°-30°</td> <td></td> <td>±0.20</td> <td></td> <td></td> </tr> <tr> <td>5°-10°</td> <td></td> <td>±0.15</td> <td></td> <td></td> </tr> <tr> <td></td> <td></td> <td>±0.10</td> <td></td> <td></td> </tr> </table>							30°	ØL	±0.30	ANGLE	±2°	10°-30°		±0.20			5°-10°		±0.15					±0.10		
30°	ØL	±0.30	ANGLE	±2°																						
10°-30°		±0.20																								
5°-10°		±0.15																								
		±0.10																								
TITLE:		RJ CONNECTOR																								
PART NO.		RJ11-6W11-DDN-BB-62-G1																								
UNIT: mm		SCALE: 1:1		PROJ. 																						
DRAWING NO.		SHEET 1 OF 1																								