



PC Board Layout
Component Side Shown

NOTES:
MATERIAL:

- 1.HOUSING MATERIAL :GLASS FILLED POLYESTER UL94V-0.
- 2.CONTACT MATERIAL :PHOSPHOR BRONZE $\phi=0.45\text{mm}$.
- 3.PLATING :GOLD PLATING F U"~50u"OVER NICKEL

ELECTRICAL:

- 1.VOLTAGE RATING :125 VAC RMS.
- 2.CURRENT RATING :1.5 AMP.
- 3.CONTACT RESISTANCE :30 MILLIOHMS MAX.
- 4.INSULATION RESISTANCE :500 MEGOHMS MIN @ 500V DC .
- 5.DIELECTRIC WITHSTANDING RESISTANCE

MECHANICAL:

- 1.DURRABILITY: :750 CYCLES MIN.
 - 2.PCB RETENTION PRE-SOLDER :1 LB MIN.
- ENVIRONMENTAL:
- 1.STORAGE : -40°C TD 85°C.
 - 2.OPERATION : 0°C TD 70°C.

APPROVALS		DATE	<p>深圳市联丰电子有限公司 SHENZHEN LINFENGYING ELECTRONIC CO.,LTD</p>
DRAWN	ZHIWEI,CHEN	2015.07.07	
CHECKED			
APPROVALS		TITLE:	RJ CONNECTOR
TOLERANCES ARE		PART NO.	RJ11-9W11-DDN-BB-66-B1
30°	∅L	+0.30	SCALE: 1:1
10°-30°		+0.20	PROJ.
5°-10°		+0.15	
-5°		+0.10	SHEET 1 OF 1

ECN NO.	REV.	DATE.	DESCRIPTION.	CHANGE.	CHECK.	APPRO.
	A		NEW			