



NOTES:

MATERIAL :

- 1.HOUSING MATERIAL :GLASS FILLED POLYESTER UL94V-0.
- 2.CONTACT MATERIAL :PHOSPHOR BRONZE φ0.45mm.
- 3.PLATING :GOLD PLATING Fu" 50u" OVER NICKEL.

ELECTRICAL:

- 1.VOLTAGE RATING :125 VAC RMS.
- 2.CURRENT RATING :15 AMP.
- 3.CONTACT RESISTANCE :30 MILLIOHMS MAX.
- 4.INSULATION RESISTANCE :500 MEGOHMS MIN @ 500V DC .
- 5.DIELECTRIC WITHSTANDING RESISTANCE :1000V AC RMS 50HZ. 1MIN.

MECHANICAL:

- 1.DURRABILITY :750 CYCLES MIN.
- 2.PCB RETENTION PRE-SOLDER :1 LB MIN.

ENVIRONMENTAL:

- 1.STORAGE : -40℃~+85℃
- 2.OPERATION : 0℃ TO 70℃.

PC Board Layout  
Component Side Shown

APPROVALS		DATE	<b>深圳市联丰电子有限公司</b> SHENZHEN LIANFENGYING ELECTRONIC CO.,LTD	
DRAWN	ZHIWEI CHEN	2015.07.07	TITLE:	RJ CONNECTOR
CHECKED			PART NO.	RJ45-9W11-DDN-BB-88-B1
APPROVALS			UNIT: mm	SCALE: 1:1
TOLERANCES ARE				PROJ.
				SHEET 1 OF 1

ECN NO.	REV.	DATE.	DESCRIPTION.	CHANGE.	CHECK.	APPRO.
	A		NEW			